

Supporting information

SF₆ catalytic degradation in a γ-Al₂O₃ packed bed plasma system: A combined experimental and theoretical study

Zhaolun Cui ^{1,3}, Chang Zhou ², Amin Jafarzadeh ³, Shengyan Meng ⁴, Yanhui Yi ⁴, Yufei Wang ², Xiaoxing Zhang ^{2*}, Yanpeng Hao ¹, Licheng Li ¹, Annemie Bogaerts ³

¹ School of Electric Power Engineering, South China University of Technology, Guangzhou 510630, China

² School of Electrical and Electronic Engineering, Hubei University of Technology, Wuhan, 430068, China

³ Research group PLASMANT, Department of Chemistry, University of Antwerp, Universiteitsplein 1, BE-2610 Wilrijk-Antwerp, Belgium

⁴ State Key Laboratory of Fine Chemicals, School of Chemical Engineering, Dalian University of Technology, Dalian 116024, P.R. China

Correspondence

Xiaoxing Zhang, School of Electrical and Electronic Engineering, Hubei University of Technology, Wuhan, 430068, China

Email: xiaoxing.zhang@outlook.com




Fig.S1. Discharge images of three packing systems. (a) 1 mm, (b) 2 mm, (c) 4 mm (100 mL/min, 3% SF₆-97 % Ar, 80W)




Fig.S2. FTIR spectra of the three packing systems (3% SF₆-97% Ar, 80 W, 100 mL/min)




Fig.S3. N₂-TPR results of the γ -Al₂O₃ pellets




Fig.S4. XRD patterns of the γ -Al₂O₃ pellets (a) fresh, (b) spent




Fig.S5. XPS patterns of the γ -Al₂O₃ pellets (a) fresh, (b) spent




Fig.S6. Typical adsorption sites on $\gamma\text{-Al}_2\text{O}_3(110)$ surface